










# QuattroSpir



EN 856 4SH - SAE R9

- APPLICATION** : Very high-pressure applications used for petroleum based hydraulic fluids
- SPECIFICATIONS** : EN 856 4SH - SAE R9 – ISO 3862-1 4SH – MT / T98 4SPH
- TEMPERATURE** : -40°F to +212°F (-40°C to +100°C)
- TUBE** : Oil resistant synthetic rubber
- REINFORCEMENT** : Four high tensile steel spiral
- COVER** : Synthetic rubber with high abrasion, ozone and weather resistance. Fire resistant with MSHA approval
- FEATURES** : Extreme Abrasion resistant UHMWPE Cover – High temperature (up to 200°C) – Low Temperature (down to -50°C)

ITEM CODE	 ID			 ROD		 OD		 MAX WP		 MIN BP		 BR	 W
	DASH	DN	INCH	MM	INCH	MM	INCH	BAR	PSI	BAR	PSI	MM	KG/M
PR-00-4SH-12	-12	19	3/4"	28.2	1.11	31.9	1.26	420	6090	1680	24360	280	1.55
PR-00-4SH-16	-16	25	1"	35.1	1.38	38.1	1.50	380	5510	1520	22040	340	2.00
PR-00-4SH-20	-20	31	1 1/4"	42.2	1.66	45.0	1.77	350	5100	1300	18855	460	2.46
PR-00-4SH-24	-24	38	1 1/2"	49.1	1.93	53.1	2.09	300	4350	1160	16820	560	3.36

Impulse tested over 1,000,000 cycles without leakage

Layline Sample

 primo	 QuattroSpir 4SH	3/4"	(19mm)	EN 856-SAE R9 Flame Resistant	420 Bar	6090 Psi
---	---	------	--------	----------------------------------	---------	----------