

AQUAFORZA 10

Water Suction & Discharge Hose



APPLICATION : Water suction and discharge in industrial and construction services

TEMPERATURE : -13°F to +158°F (-25°C to +70°C)

REINFORCEMENT : High tensile synthetic textile and steel helix wire

COVER : Abrasion and weather resistant synthetic rubber

TUBE : Natural and Synthetic rubber

ITEM CODE	ID		OD	MAX WP		MIN BP		VACUUM
	INCH	MM	MM	BAR	PSI	BAR	PSI	BAR
PR-00-AQ10-16	1"	25.4	36	10	145	30	435	0.8
PR-00-AQ10-20	1 1/4"	31.8	44	10	145	30	435	0.8
PR-00-AQ10-24	1 1/2"	38.1	51	10	145	30	435	0.8
PR-00-AQ10-32	2"	50.8	64	10	145	30	435	0.8
PR-00-AQ10-40	2 1/2"	63.5	77	10	145	30	435	0.8
PR-00-AQ10-48	3"	76.2	90	10	145	30	435	0.8
PR-00-AQ10-64	4"	101.6	118	10	145	30	435	0.8
PR-00-AQ10-96	6"	152.4	170	10	145	30	435	0.8
PR-00-AQ10-128	8"	203.2	224	10	145	30	435	0.8
PR-00-AQ10-160	10"	254	276	10	145	30	435	0.8
PR-00-AQ10-192	12"	304	326	10	145	30	435	0.8

Layline Sample

