






# Primo

## PVC Steel Wire Hose



- APPLICATION** : Suction and discharge of water, oil and powder in the factories, agriculture, engineering, foodstuffs
- TEMPERATURE** : +15°F to +160°F (-9°C to +71°C)
- CONSTRUCTION** : Tube and cover – PVC
- REINFORCEMENT** : Steel helical wire
- FEATURES** : Good adaptability to hard weather conditions and vacuum pressure. Light transparent with small bending radius

ITEM CODE	ID 		OD 	VACUUM 		MAX WP 		MIN BP 	
	INCH	MM	MM	BAR	PSI	BAR	PSI	BAR	PSI
PR-00-PSWH-08	1/2"	12	18	-1	-15	10	145	30	435
PR-00-PSWH-12	3/4"	20	24.5	-1	-15	8	116	20	290
PR-00-PSWH-16	1"	25	32	-1	-15	7	102	20	290
PR-00-PSWH-20	1 1/4"	32	41	-1	-15	7	102	20	290
PR-00-PSWH-24	1 1/2"	38	45	-1	-15	6	87	18	261
PR-00-PSWH-32	2'	50	58.2	-1	-15	5	73	14	203
PR-00-PSWH-40	2 1/2"	64	72	-1	-15	4	58	10	145
PR-00-PSWH-48	3"	75	84	-1	-15	4	58	10	145
PR-00-PSWH-96	6"	152	168	-1	-15	3	44	10	145

### Layline Sample

