



PrimaCor

PVC Lay Flat Hose

APPLICATION : Irrigation, construction, industrial, agricultural, mining, portable hydrant, relay supply line, quarry

TEMPERATURE : -5°F to +170°F (-20°C to +76°C)

CONSTRUCTION : Medium: Features a balanced polyester yarn spiral wrap, longitudinal strength member and homogeneous PVC tube and cover to prevent separation.




Heavy: Premium quality PVC tube and cover, reinforced with two spiral plies and longitudinal synthetic cords.

FEATURES : Medium: Smooth tube to provide low friction loss, with Ultraviolet inhibitors to reduce aging.

Heavy: MSHA accepted – use as a water hose in underground mining applications.

Provides higher working pressure and resist kinking and twisting.

MEDIUM DUTY

ITEM CODE	ID 		MAX WP 		MIN BP 	
	INCH	MM	BAR	PSI	BAR	PSI
PR-00-LF4-48	3"	76	4	58	12	174
PR-00-LF4-64	4"	102	4	58	12	174
PR-00-LF4-96	6"	153	4	58	12	174
PR-00-LF4-128	8"	203	4	58	12	174
PR-00-LF4-160	10"	254	4	58	12	174
PR-00-LF4-192	12"	305	4	58	12	174

HEAVY DUTY

PR-00-LF8-128	8"	203	8	116	24	348
---------------	----	-----	---	-----	----	-----

Layline Sample

