

PrimeFlex






PVC Suction Hose



APPLICATION : Suction and delivery of water, salt water, light chemicals, liquids etc. in agricultural, industrial applications , constructions, sewer purging, sludge, slurries, waste matter, sand and gravel, etc.

TEMPERATURE : -40°F to +122°F (-40°C to +50°C)

CONSTRUCTION : Strong, flexible and smooth special superelastic material, shock resistant PVC spiral, crushing, chemical agents, abrasion and weather resistant, corrugated sliding outside

ITEM CODE	ID 		OD 	WT 	MAX WP 		BR 
	INCH	MM	MM	MM	BAR	PSI	MM
PR-00-PF-16	1"	25.4 ± 0.5	29.4±0.5	2.0	5.0	75	70
PR-00-PF-24	1 1/2"	38.1 ± 0.5	44.1±0.5	3.0	5.0	75	110
PR-00-PF-32	2"	50.8 ± 1.0	57.8±1.0	3.5	5.0	75	150
PR-00-PF-40	2 1/2"	63.5 ± 1.0	70.5±1.0	3.5	4.0	60	180
PR-00-PF-48	3"	76.2 ± 1.0	84.2±1.0	4.0	4.0	60	220
PR-00-PF-64	4"	101.6 ± 1.5	111.6±1.5	5.0	4.0	60	330
PR-00-PF-96	6"	152.4 ± 1.5	166.4±1.5	7.0	3.0	45	700

Layline Sample

